



Hillside Slides Model Mountain Lake

Specifications

Description: Dual 32" I.D. closed flume fiberglass slides with semi-transparent sections on upper half of flume

Centerline Run: 76' 0" (1) & 81' 9" (2)

Features

- 32" inside diameter closed fiberglass flume.
- Flume: ultra violet stabilized gelcoat.
- Stairs & Platform: available.
- Stainless steel base plates, hardware and anchor bolts.
- Flume posts are required in accordance to the elevation.
- 40 gpm water flow (each flume) recommended; 40 to 60 gpm required.
- Splash down dimension 12' 8" x 20' 0"
- Minimum water depth: 3' 0"
- USA Made

Flume 1: Lime Green Flume
Flume 2: Tangerine Flume

Entry Height: 14' 10"

Platform Size: *Platform done by others.

Space Requirements: 46' 0" x 35' 9"

Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: (a) 48" width; (b) Inner handrails (if applicable); (c) Spiral stairs.
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.

*Space requirements may vary with options chosen.



PO Box 270, Baker City, OR 97814
(541) 523-0224 (800) 252-8475 Fax (541) 523-0231
www.naturalstructures.com - info@naturalstructures.com