



Fiberglass Water Slide Model 1949

Specifications

Description: Single open & closed fiberglass flume water slide featuring 360° curve.

Centerline Run: 103' 5"

Entry Height: 37' 9-11/16"

Platform Size: N/A Tower and stairs by others

Space Requirements: 12' 7" x 64' 11 1/2" *

Features

- 32" inside diameter closed fiberglass flume.
- 36" inside diameter open fiberglass flume.
- Flume: ultra violet stabilized gelcoat.
- Platform & Stairs: By others
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- 500-700 gpm water flow required.
- Minimum water depth: 3' 0"
- USA Made

Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: (a) 48" width; (b) Inner handrails (if applicable); (c) Spiral stairs.
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270 • Baker City OR 97814 • 800-252-8475 • www.naturalstructures.com • Email: info@naturalstructures.com

*Space requirements may vary with options chosen.